

Montelli[®] Surfaces


Montelli[®] Surfaces is a decorative material, which can be used in a variety of interior applications in both commercial and residential sectors. A composite product, Montelli[®] Surfaces is produced by a continuous casting process, meeting strict quality control standards.

It is supplied in sheets and can be used to create wall panels, coffee tables, reception desks, kitchen countertops, bathroom vanities and shower surrounds, as well as many other applications. Because the material is solid, and uniform right through the surface is durable, non-porous, hygienic and repairable. These performance benefits make Montelli® Surfaces a suitable material for areas subject to heavy use. Montelli® sheets can be cut, routed, joined with inconspicuous seams, sanded and engraved to create a wide variety of designs, color inlays and effects.


Colors of Montelli[®] Surfaces 204 (MG204) 101 (MS101) 201 (MG201P) 207 (MG207) 231 (MG231) LOTUS ARCTIC WHITE SNOW DRIFT PEARL WHITE **IVORY MIST** 12mm 12 mm 12mm 12mm 12mm 282 (MG282) 288 (MG288) 306 (MP306) 1201 (MG1201) 1202 (MG1202) GREY GRATINO PEPPER GREY BLIZZARD CICADA WINGS FOGGY ICFLAND 12mm 12 mm 12mm 12mm 12_{mm} 1303 (MP1303) 1213 (M1213) 1457 (M1457) 1458 (M1458) 1459 (M1459) SILVERY SAND LILY POND MOSS BARK NUT 12mm 12mm 12mm 12mm 12mm 1461 (M1461) 1462 (M1462) 2530 (M2530) 2565 (M2565) 2586 (M2586) CREPUSCULE PENUMBRA ICELAND SNOWFIELD HAIL STORM SNOW IADE 12mm 12mm 12mm 12mm 12mm

() China Color Code

Montelli[®] Surfaces on Kitchen Surfaces



Edge Types



Montelli® Surfaces Competitive Advantages

		4000	Lanna L	GRAMIT	Chappy	MONTELLI®
	Seamless joints surface integrally	x	×	×	x	\checkmark
	Seamless connection with sink	×	×	×	x	\checkmark
sign	Seamless connection with a kitchen apron (Rear rim)	x	×	x	x	~
of de	Seamless insertion of Montelli® other colors	x	x	x	x	\checkmark
Freedom of design	Solid edge with antiperelivom	\checkmark	x	\checkmark	\checkmark	\checkmark
eed	Unbounded leading edge design	×	x	\checkmark	\checkmark	\checkmark
F	Flush drains	x	x	\checkmark	\checkmark	\checkmark
	Any form of flat countertop	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
	Built-in holders for hot dishes	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
tics	The choice of surface polishing	×	x	\checkmark	\checkmark	\checkmark
	Pearly luster	×	x	×	×	\checkmark
Aesthetics	The legacy of the Italian aesthetics and paints	x	x	x	x	\checkmark
Ae	The perfect combination of more than 1000 shades wood (cabinet doors)	×	x	x	×	\checkmark
Hygiene	Easy to care for a seamless surface	×	x	×	x	\checkmark
	Non-porous (does not absorb moisture)	x	×	x	x	\checkmark
	Easy stain removal with household cleaners	×	\checkmark	\checkmark	\checkmark	\checkmark
Durability	Easily renewable 'At home'	x	x	x	x	\checkmark
	Easily repairable 'At home'	×	x	×	×	\checkmark
	The absence of traces produced repair	x	×	x	×	\checkmark
D	Impact resistance	×	x	\checkmark	\checkmark	\checkmark

Comparison of Montelli® Surfaces with other surface materials

Technical Data

PROPERTY	TYPICAL RESULT	REQUIREMENT	TEST METHOD	REF.
Flexural stress	55.19 MPa		EN ISO 178	2
Flexural modulus	9463.2 MPa		EN ISO 178	2
Deflection	3.412 mm		EN ISO 178	2
Tensile strength	38.4 MPa		EN ISO 527-2	3
Deformation	0.51 %		EN ISO 527-2	3
Surface defects	No failure	Max. contamination area < 1.0 mm²/m²	ISO 19172-2 Clause 5	1
Consistency of color	No noticeable change on base color along the seam		ISO 19172-2 Clause 6	1
Load test	No cracks/no breaks	Residual deflection <0,25 mm	ISO 19172-2 Clause 7	1
Resistance to impact by large- diameter ball	No breakage	Imprint <10mm	ISO 19172-2 Clause 8	1
Light fastness (Xenon Arc)	5* - No changes	Not worse than 4*	ISO 19172-2 Clause 9	1
Stain/ chemical resistance	Rating 4/5*	Not worse than 3*	ISO 19172-2 Clause 10.1	1
Resistance to cigarette burns	Rating 3/4*	Not worse than 2*	ISO 19172-2 Clause 11	1
Resistance to dry heat (180° C)	Rating 5*	Not worse than 3*	ISO 19172-2 Clause 12	1
Resistance to wet heat	Rating 5*	Not worse than 3*	ISO 19172-2 Clause 13	1
Hot/cold water cycle resistance	No failure	No failure	ISO 19172-2 Clause 14	1
Hardness (Barcol)	60 ±3 (HRM)		ISO 19172-2 Clause 15	1
Hardness (Ball indentation)	290 ±23 (N/mm²)		ISO 19172-2 Clause 15	1
Hardness (Rockwell)	88 ±1 (HRM)		ISO 19172-2 Clause 15	1
Dimensional stability (humidity (90 ±5) % RH and (23±2) °C)	-0.02 Longitudinal, -0.05 Transversal		ISO 4596-2 Clause 11	1
Dimensional stability (humidity (15 ±5) % RH and (23±) ° C)	0.04 Longitudinal, 0.06 Transversal		ISO 4586-2 Clause 11	1
Resistance to immersion in boiling water	Increases < 2% , Rating 4*	Increases < 2%, Shine not worse than 4*	ISO 4586-2 Clause 7	1
Resistance to surface wear	0.02 % Surface wear for 25 revolutions		ISO 4586-2 Clause 6	1

* Rating 5: no visible change

* Rating 4: minor change of shine and/or colour-only visible at certain angles of view

* Rating 3: moderate change of shine and/or colour

* Rating 2: distinct change of shine and/or colour

* Rating 1: surface damage and/or blistering

(1) Aimplas report 21-0091-EN/2 – 9/4/2021

(2) Sirris report 21-1599-Labtool s200065-flexion – 19/4/2021

(3) Sirris report 21-1571-Labtool s200065-traction – 19/4/2021

Typical results for 12mm thick material in solid colours. Properties may vary by aesthetic. These values are not intended for engineering calculations.

To know more about Montelli®: www.montelli.com

Montelli®

DuPont¹⁰, the DuPont¹⁰ Oval Logo and Montelli⁰ are trademarks or registered trademarks of affiliates of DuPont de Nemours Inc. © Copyright 2022 of affiliates of DuPont de Nemours Inc., all rights reserved.